CENTER 200/201 Mini AC, AC/DC Clamp Meter

CENTER 200 series are our mini clamp meters. These clamps are designed with great hand held feeling and easily fit in the pocket. With the range 400A and the resolution is 0.01A that will fit most needs of an electrician. With built-in Voltage and Continuity functions, these testers are good choices for an everyday instrument in the tool box.

200 AC CLAMP METER

201 AC/DC CLAMP METER

FEATURES:

- AC/DC Current (201)
- Pocket Size
- High Speed Bargraph
- Data Hold Function
- Touch Zero Function
- Autoranging
- Auto Power Off
- Resolution 0.01A, 0.1V
- Measuring Frequency From Current Clamp & Test Terminal

CE 300V CAT III 600V CAT II

CENTER 202 Mini AC Clamp Meter (True RMS)

CENTER 202 is for users who need True RMS AC current measurements.

FEATURES:

- True RMS
- Autoranging
- Auto Power Off
- High Speed Bargraph
- Data Hold Function

CE 300V CAT III 600V CAT II

SPECIFICATIONS

Function	Range	Resolution	Accuracy
ACA	40A ~ 400A	0.01A ~ 0.1A	±1.9%rdg + 5dgts
DCA	40A ~ 400A	0.01A ~ 0.1A	±2.5%rdg + 5dgts
ACV	400V ~ 600V	0.1V ~ 1V	±1.5%rdg + 5dgts
DCV	400V ~ 600V	0.1V ~ 1V	±1%rdg + 2dgts
Ohms	400Ω	0.1Ω	±1%rdg + 2dgts
Hz(A)	20Hz ~ 10KHz	1Hz ~ 10Hz	±0.1%rdg + 1dgts
Hz(V)	10Hz ~ 1MHz	1Hz ~ 1KHz	±0.1%rdg + 1dgts
·ı))	Active Sound Level: ≦40Ω		

Display	3-3/4 digital(4000 count) display
Sampling Rate	2 times/sec(digital reading) 20 times/sec(analog bar indication)
Battery	1.5V, size AAA battery x 2
Dimensions	193x50x28 mm
Weight	approx.240g
Jaw Opening Diameter	25mm(200/202), 30mm(201)