CENTER 384 Hydrogen (H_2) Gas Leak Detector

CENTER 384 **Track Gas Leak Detector** can detector mixture 5% Hydrogen (H2) + 95% Nitrogen(N) with extremely sensitivity. The unit is built in newly developed heated semi-conductor sensor and microprocessor control to provide reliable digital signal processing. Adjustable leak sensitivity level and 7 LED visual indicators also offer the users the ease and convenience of operations. It can **detect less that 5 ppm Hydrogen concentration.**

KEY SPECIFICATIONS/SPECIAL FEATURES

- Detectable Gases:
  mixture 5% Hydrogen (H2) + 95% Nitrogen(N).
- Sensitivity: Less than 5 ppm ; 2g/year
- Sensor life: approx. 1 year
- Response Time: Instantaneous
- Warm up time: 45 seconds
- DC brushless fan.
- High-median-Low leak sensitivity selector.
- 15.5" (40 CM) flexible stainless probe.
- Ambient concentration reset.
- Automatic zero and background compensation.
- Carrying case included.
- Operating Temperature & Humidity:
  0 ~40 °C, < 80% RH
- Dimension / Weight:
  173 x 66 x 56 mm (approx. 400g)
- Power Source:
  4 AA (6V DC) size Alkaline Batteries
- Battery Life: Approx.7 hours normal use.

GlobalGROUP ISO 9001 UKAS QUALITY MANAGEMENT 039
Certificate No. 49Q13377

CE Accordance With EN35422 and EN14624, CE Design

* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER®
CENTER TECHNOLOGY CORP.
4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,
New Taipei City 238, Taiwan
TEL: 886-2-26763926 E-Mail : center@centertek.com
FAX: 886-2-26763925 http : //www.centertek.com

Distributed by: